

IN THE CLAIMS

Applicant hereby presents the claims, their status in the application, and amendments thereto as indicated:

1. (Currently Amended) A support member comprising a plurality of wood plies and having a tenon portion atop a unitary body portion, wherein:  
at least part of the tenon portion extending extends outwardly from the body portion, the body portion being the only structure supporting the tenon portion, wherein each ply is joined to at least one other ply at one of a plurality of interfaces, and each ply has a grain which is oriented in a different direction relative to grains of adjacent plies.
2. (Original) The support member of claim 1, wherein the interfaces are generally parallel along a longitudinal direction of the support member
3. (Original) The support member of claim 1, wherein each ply has a grain that is approximately orthogonal to grains of adjacent plies.
4. (Original) The support member of claim 1, wherein the tenon portion extends outwardly by a distance that is at least as great as a width of the body portion.
5. (Original) The support member of claim 1, wherein the tenon portion extends outwardly from at least two sides of the body portion.
6. (Original) The support member of claim 1 further comprising a foot protector disposed about a foot portion of the support member, the foot portion being on an opposite side of the body portion from the tenon portion.

7. (Currently Amended) A support member comprising a plurality of wood plies and having a first tenon portion, a unitary body portion, and an outwardly extending second tenon portion therebetween, wherein:

the body portion is the only structure supporting the first and second tenon portions.

each ply is joined to at least one other ply at one of a plurality of interfaces, the interfaces being generally parallel along a longitudinal direction of the support member, and

each ply has a grain that is approximately orthogonal to grains of adjacent plies.

8. (Original) The support member of claim 7, wherein the second tenon portion extends outwardly by a distance that is at least as great as a width of the body portion.

9. (Original) The support member of claim 7, wherein the second tenon portion extends outwardly from at least two sides of the body portion.

10. (Original) The support member of claim 7 further comprising a foot protector disposed about a foot portion of the support member, the foot portion being on an opposite side of the body portion from the second tenon portion.

11. (Currently Amended) A support member comprising a plurality of wood plies and having a first tenon portion, a unitary body portion, and an outwardly extending second tenon portion therebetween, wherein:

the body portion is the only structure supporting the first and second tenon portions.

each ply is joined to at least one other ply at one of a plurality of interfaces, the interfaces being generally parallel along a longitudinal direction of the support member, and

each ply has a grain that is approximately orthogonal to grains of adjacent plies, and wherein, ~~except in the longitudinal direction,~~

the first tenon portion and the body portion ~~are similarly proportioned~~ have approximately the same widths.

12. (Original) The support member of claim 11, wherein the second tenon portion extends outwardly by a distance that is at least as great as a width of the body portion.

13. (Original) The support member of claim 11, wherein the second tenon portion extends outwardly from at least two sides of the body portion.

14. (Original) The support member of claim 11 further comprising a foot protector disposed about a foot portion of the support member, the foot portion being on an opposite side of the body portion from the second tenon portion.

15. (Currently Amended) A table comprising  
at least one leg having a first tenon portion atop an outward extending second tenon portion atop a unitary body portion and being formed from a plurality of wood plies, wherein each ply is joined to at least one other ply at one of a plurality of interfaces, the interfaces being generally parallel along a longitudinal direction of the leg, ~~and each ply has a grain that is approximately orthogonal to grains of adjacent plies,~~ and the body portion is the only structure supporting the first and second tenon portions; and

a top having at least one mortise on one side thereof into which at least the first tenon portion of the leg is secured.

16. (Original) The table of claim 15, wherein each mortise is formed to compliment at least the first tenon portion of each leg, respectively.

17. (Original) The table of claim 15, wherein each mortise extends through the top.

18. (Original) The table of claim 15 further comprising at least one foot protector disposed about a foot portion of the support member, the foot portion being on an opposite side of the body portion from the second tenon portion.

19. (Original) The table of claim 15, wherein, except in the longitudinal direction, the first tenon portion and the body portion of each leg are similarly proportioned.

20. (Original) The table of claim 15, wherein the second tenon portion of each leg extends outwardly by a distance that is at least as great as a width of the body portion.

21. (Original) The table of claim 15, wherein the second tenon portion of each leg extends outwardly from at least two sides of the body portion.

22. (Currently Amended) A table comprising  
at least one leg having a first tenon portion atop an outward extending second tenon portion atop a body portion, wherein the leg includes a plurality of wood plies, each ply is joined to at least one other ply at one of a plurality of interfaces, the interfaces being generally parallel along a longitudinal direction of the leg, and each ply having a grain that is approximately orthogonal to grains of adjacent plies, and wherein, except in the longitudinal direction, the first tenon portion and the body portion of each leg are similarly proportioned;

a top having at least one mortise on one side thereof into which the first and second tenon portions of the leg are secured; and

at least one foot protector disposed about a foot portion of each leg, respectively, the foot portion being on an opposite side of the body portion from the second tenon portion and including a plurality of wood plies.

23. (Original) The table of claim 22, wherein each mortise is formed to compliment the first and second tenon portions of each leg, respectively.

24. (Original) The table of claim 22, wherein each mortise extends through the top.

25. (Original) The table of claim 22, wherein the second tenon portion of each leg extends outwardly by a distance that is at least as great as a width of the body portion.

26. (Original) The table of claim 22, wherein the second tenon portion of each leg extends outwardly from at least two sides of the body portion.

27. (New) The table of claim 22, wherein the wood plies of each foot protector are orthogonal to the wood plies of each respective leg.